Ice-O-Matic

PROJECT: _____

ITEM # _____ QTY: _____

MODEL # _____

AIA # _____ SIS # _____

CUBE ICE MAKER


CUBE ICE MAKER

CIM1446HA49



Features and Benefits

- Modular design with dual exhaust for flexible application and easy installation on top of bins or dispensers.
- Easy to clean with front facing evaporator.
- Dishwasher safe plastic components (up to 180°F).
- Easy and quick cleaning reducing operating costs.
- Simple to service with many common parts across all CIM machines.
- Harvest Assist provides consistent ice production for the life of the ice maker while reducing energy consumption and increasing capacity.
- Electroless nickel plating on all evaporator plates ensures reliability and durability.
- Constructed from corrosion-resistant and fingerprint-proof aluminum.



ICE FORMS	
HALF CUBE	3/8 x 7/8 x 7/8 in.
	10 x 22 x 22 mm

BIN CHART

Model #	B40	B42	B55	B110	B60-1330	B60-1660
capacity width	344 lbs (156 kg) 30 in (762 mm)	351 lbs (160 kg) 22 in (559 mm)	510 lbs (232 kg) 30 in (762 mm)	854 lbs (388 kg) 48 in (1,219 mm)	1,330 lbs (603 kg) 60 in (1,524 mm)	1,660 lbs (752 kg) 60 in (1,524 mm)
Kit for combining wider bins with smaller models	Not Compatible	Not Compatible	Not Compatible	Kit Not Required	Kit Not Required	Kit Not Required

See Ice-O-Matic Catalog for Adapter Kits to combine ice makers with most available ice/beverage dispensers.



CIM1446HA49 shown atop of bin B110 (sold separately)

Warranty

- Ice Maker: **3 years parts and labor**
- Evaporator and Compressor: **5 years parts**
- Evaporator:**7 years parts and labor**
  (if enrolled in the filter program for US & Canada)

Options & Accessories

- KSI-1 - Safe Ice Module
- KCUBEDISPB for ice level control for a dispenser - verify adapter with disp. manufacturer
- B110

Water Filter

- Manifold System IFQ1-M gets replacement filter IOMQ-M

11100 E. 45th Avenue • Denver, CO 80239
Phone: 1.866.PURE.ICE
www.iceomatic.com

Rev. 10/2026 Printed in U.S.A.

Specifications are subject to change without prior notice.


APPROVAL: _____ DATE: _____

Ice-O-Matic CUBE ICE MAKER


CIM1446HA49

Line drawing note: Numbers with quote symbol " are in inches. Numbers enclosed in [brackets] are in millimeters.


PLAN / TOP VIEW



ELEVATION / FRONT VIEW



UTILITIES / BACK VIEW



Air Cooled

A. Ice Maker Drain, 3/4" FPT
B. Ice Maker Potable Water Inlet, 3/8" FPT
C. Electrical Connection, Ø.875" [22.2] (2)
D. Condensate Base Drain, Ø.50" [12.7]

SPECIFICATIONS	
Model	CIM1446HA49
Condensing Type	Air
Voltage/Hertz/Phase	208-230/60/1
Min. Circuit Amp	18.9
Max Breaker Size	30 A
kWH per 100 lbs of ice at 70ºF air / 50ºF water	3.1
kWH per 100 lbs of ice at 90ºF air / 70ºF water	4.22
BTU (approx per hour)	23400
Number of Wires	3 (including ground)
Refrigerant	R449A
Refrigeration Charge	58 oz

Ice Production per 24 hrs	
70º air / 50º water lbs (kg)	90º air / 70º water lbs (kg)
1600 (726)	1212 (550)

Water Usage gallons per 100 lbs of ice 90ºF air / 70ºF water	
Potable	Condenser
15.2	N/A

OPERATING REQUIREMENTS		
	MINIMUM	MAXIMUM
Ambient Temp. Range Air	50°F (10°C)	100°F (38°C)
Water Temp	40°F (4°C)	100°F (38°C)
Water Pressure	20 PSIG (1.4 BAR)	80 PSIG (5.5 BAR)

DIMENSIONS		
Unit Width	48.25	1226
Unit Depth	24.25	616
Unit Height	26.84	682

Shipping Weight	318 lbs / 144 kg
Shipping Dimensions (in.)	51 (W) x 27 (D) x 33 (H)
Shipping Dimensions (mm)	1295 (W) x 686 (D) x 838 (H)

We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment.

Rev. 10/2026 Printed in U.S.A.

11100 E. 45th Avenue • Denver, CO 80239 • Phone: 1.866.PURE.ICE • www.iceomatic.com

WELBILT
an Ali Group Company